

AGRI-VAC 5614



WALINGA®
TOUGH TO BEAT IN THE LONG RUN



SPECIFICATIONS FOR: Walinga Pneumatic Grain Moving Unit Model 5614

	5614 PC	5614 DLX
HEIGHT	92" (234 cm)	92" (234 cm)
WIDTH	92" (234 cm)	92" (234 cm)
LENGTH	103" (261 cm)	103" (261 cm)
WEIGHT	2352 lbs (1069 kg)	2552 lbs (1160 kg)
DISCHARGE HEIGHT	13' - 8" minimum (4.17 m)	13' - 8" minimum (4.17 m)
HP REQUIRED	70 - 85 hp	70 - 85 hp
PTO SPEED	1000 RPM	1000 RPM
LINE SIZE	5" (125 cm)	5" (125 cm)
TIRES	Two standard farm implement	Two standard farm implement
WHEELS	15" (38 cm), 5 stud	15" (38 cm), 5 stud
BLOWER	#614 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower	#614 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower
AIRLOCK	#1314 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation	#1314 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation
DRIVE	Tongue mounted drive shaft with V-type 5 groove sheaves & belts	Tongue mounted drive shaft with V-type 5 groove sheaves & belts
HYDRAULICS	Hoses & quick couplings Open/closed centre system	Self Contained
RECEIVER	24" dia. (61 cm) two piece, single inlet	24" dia. (61 cm) two piece, dual inlets
PRECLEANER	20" dia. (51 cm)	20" dia. (51 cm)
SAFETY	Vacuum/Pressure relief valves	Vacuum/Pressure relief valves

5614 & 5614 DLX

CAPACITY*	Bu/hr*	Tonnes/hr*
Corn & Barley	2500	64
Wheat	2200	58
Soybeans	1900	51

Due to continuous product development, specifications are subject to change without notice. Some items shown may be optional.

*Capacities based on using 12' (3.65 m) suction line and truck loading kit. Capacity will vary with condition of product.

5614

AVAILABLE OPTIONS

- 540 PTO speed
- Hydraulic Boom Rotation
- Dual inlets on 5614
- Self contained hydraulics on 5614
- Full Rhino Lined Receiver Tank and boom cyclone
- Super Hardened Airlock
- Stainless steel delivery lines

STANDARD ACCESSORIES

- Hose carrier
- Precleaner on 5614
- Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower
- 5" (125 mm) clean-up hose package
- Manual rotation with hydraulic lift; truck loading kit with cyclone
- Two 5" dia. x 12' (125 mm x 3.65 m) galvanized steel delivery lines (DLX models comes with Stainless Steel Hoses)
- One 5" dia. (125 mm) suction nozzle
- One 5" dia. x 12' (125 mm x 3.65 m) rubber clean-up hose with swivel coupling
- One 5" dia. (125 mm) suction nozzle with clean-up attachment floor sweep with wheels
- Rhino Liner covering high wear areas in receiver tank and boom cyclone

Suction
Nozzle



Floor Sweep Nozzle



5614 DLX
REAR VIEW

WALINGA.COM

Head Office

R.R. #5,
Guelph, Ontario
Canada N1H 6J2
Tel: 519.824.8520
Tel: 888.925.4642
Fax: 519.824.5651

Michigan

1190 Electric Ave.
Wayland, Michigan
USA 49348
Tel: 616.877.3470
Tel: 800.466.1197
Fax: 616.877.3474

Manitoba

70 3rd Ave. N.E.
Box 1790
Carman, Manitoba
Canada R0G 0J0
Tel: 204.745.2951
Fax: 204.745.6309

Ontario

938 Glengarry Cres.
Fergus, Ontario
Canada N1M 2W6
Tel: 519.787.VACS (8227)
Fax: 519.787.8210