

AGRI-VAC 7614



WALINGA®
TOUGH TO BEAT IN THE LONG RUN



**SPECIFICATIONS FOR:
Walinga Pneumatic Grain Moving Unit Model 7614**

	7614 PC	7614 DLX
HEIGHT	96" (244 cm)	96" (244 cm)
WIDTH	92" (234 cm)	92" (234 cm)
LENGTH	107" (272 cm)	107" (272 cm)
WEIGHT	3102 lbs (1410 kg)	3302 lbs (1498 kg)
DISCHARGE HEIGHT	13' - 8" minimum (4.17 m)	13' - 8" minimum (4.17 m)
HP REQUIRED	130-150 hp	130-150 hp
PTO SPEED	1000 RPM	1000 RPM
LINE SIZE	6" (150 mm) & 7" (175 mm)	6" (150 mm) & 7" (175 mm)
TIRES	Two standard farm implement	Two standard farm implement
WHEELS	15" (38 cm), 5 stud	15" (38 cm), 5 stud
BLOWER	#614 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower	#614 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower
AIRLOCK	#2018 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation	#2018 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation
DRIVE	Tongue mounted drive shaft with V-type 5 groove sheaves & belts	Tongue mounted drive shaft with V-type 5 groove sheaves & belts
HYDRAULICS	Hoses & quick couplings Open/closed centre system	Self Contained
RECEIVER	32" dia. (81 cm) two piece, single inlet	32" dia. (81 cm) two piece, dual inlets
PRECLEANER	24" dia. (61 cm)	24" dia. (61 cm)
SAFETY	Vacuum/Pressure relief valves	Vacuum/Pressure relief valves

7614 & 7614 DLX

CAPACITY*	Bu/hr*	Tonnes/hr*
Corn & Barley	5500	140
Wheat	5000	136
Soybeans	4800	131

*Capacities based on using 12' (3.65 m) suction line and truck loading kit. Capacity will vary with condition of product. Due to continuous product development, specifications are subject to change without notice. Some items shown may be optional.

7614

AVAILABLE OPTIONS

- Self contained hydraulics on 7614
- Full Rhino Lined Receiver Tank and boom cyclone
- Stainless steel delivery lines
- Super Hardened Airlock

STANDARD ACCESSORIES

- Dual inlets on 7614
- Hose carrier
- Precleaner on 7614
- Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower
- Hydraulic-rotating truck loading kit with cyclone
- One 7" dia. x 12' (175 mm x 3.65 m) stainless steel delivery line
- 6" (150 mm) cleanup hose package
- One 7" (175 mm) dia. suction nozzle
- One 6" dia. x 12' (150 mm x 3.65 m) stainless steel delivery line
- One 6" (150 mm) dia. suction nozzle
- One 6" dia. x 12' (150 mm x 3.65 m) rubber clean-up hose with swivel coupling
- One 6" (150 mm) dia. suction nozzle with clean-up attachment floor sweep with wheels
- One 6" to 7" adapter (150 mm-175 mm)
- Rhino liner covering high wear areas in receiver tank and boom cyclone

**Suction
Nozzle**



Floor Sweep Nozzle

7614 DLX REAR VIEW

WALINGA.COM

Head Office

R.R. #5,
Guelph, Ontario
Canada N1H 6J2
Tel: 519.824.8520
Tel: 888.925.4642
Fax: 519.824.5651

Michigan

1190 Electric Ave.
Wayland, Michigan
USA 49348
Tel: 616.877.3470
Tel: 800.466.1197
Fax: 616.877.3474

Manitoba

70 3rd Ave. N.E.
Box 1790
Carman, Manitoba
Canada R0G 0J0
Tel: 204.745.2951
Fax: 204.745.6309

Ontario

938 Glengarry Cres.
Fergus, Ontario
Canada N1M 2W6
Tel: 519.787.VACS (8227)
Fax: 519.787.8210