From 116 to 2149 bushels -


We have the right size bin to meet your needs

BIN			APPROXIMATE CAPACITY (40#/CUBIC FT.)						FILL HEIGHT	
DIAMETER	NUMBER OF RINGS	LB	2000# TONS	METRIC TONS	CUBIC FEET	CUBIC METERS	BUSHELS	FEET	METERS	
6 Ft. Diameter with 60° Taper Hopper	1	5793.65	2.90	2.63	144.84	4.10	116	10' 11"	3.33	
	2	8807.69	4.40	4.00	220.19	6.24	177	13' 7"	4.14	
	3	11821.74	5.91	5.36	295.54	8.37	237	16' 3"	4.95	
	4	14835.78	7.42	6.73	370.89	10.50	298	18' 11"	5.77	
7 Ft.	1	9639.15	4.82	4.37	240.98	6.82	194	14' 7"	4.45	
Diameter with 67°	2	13741.60	6.87	6.23	343.54	9.73	276	17' 3"	5.26	
	3	17844.05	8.92	8.09	446.10	12.63	358	19' 11"	6.07	
Taper Hopper	4	21946.50	10.97	9.95	548.66	15.54	441	22' 7"	6.88	
	5	26048.94	13.02	11.82	651.22	18.44	523	25' 3"	7.70	
	6	30151.39	15.08	13.68	753.78	21.34	606	27' 11"	8.51	
9 Ft.	1	16241.89	8.12	7.37	406.05	11.50	326	15' 6"	4.72	
Diameter	2	23023.48	11.51	10.44	575.59	16.30	463	18' 2"	5.54	
with 60°	3	29805.08	14.90	13.52	745.13	21.10	599	20' 10"	6.35	
Taper Hopper	4	36586.68	18.29	16.60	914.67	25.90	735	23' 6"	7.16	
	5	43368.28	21.68	19.67	1084.21	30.70	871	26' 2"	7.98	
	6	50149.88	25.07	22.75	1253.75	35.50	1007	28' 10"	8.79	
40.51	1	34649.70	17.32	15.72	866.24	24.53	696	19' 1"	5.82	
12 Ft. Diameter with 60°	2	46705.88	23.35	21.19	1167.65	33.06	938	21' 9"	6.63	
	3	58762.05	29.38	26.65	1469.05	41.60	1180	24' 5"	7.44	
Taper Hopper	4	70818.23	35.41	32.12	1770.46	50.13	1423	27' 1"	8.26	
	5	82874.40	41.44	37.59	2071.86	58.67	1665	29' 9"	9.07	
	6	94930.58	47.47	43.06	2373.26	67.20	1907	32' 5"	9.88	
	7	106986.80	53.49	48.53	2674.67	75.74	2149	35' 1"	10.69	

Boot collar is included with all 16" opening bins listed above. 6' and 9' diameter bins are also available in 25" opening which requires an optional boot adapter. Ladders and other accessories are optional and should be ordered separately. NOTICE: All feed bins are designed for the storage of free-flowing material only. Soybean meal, meat scraps, and certain other materials are not considered to be free-flowing and should not be stored in these bins

Flexible Auger Systems

		•
	Approximate lbs./hr.*	Approximate lbs./min.*
Low Volume	900	15
Standard Volume	2700	45
High Volume	5400	90
High Moisture	3000	50
* Dates based on dry ground	norm at 40 lbs /ou ft	actual delivery rate



North America: Phone: 800-99VALCO (800-998-2526) Fax: (+1) 419-678-2200

E-mail: sales@val-co.com

LIT02007

Fax: (+1) 419-678-2200

©2013 Valco Companies, Inc.

E-mail: intl.sales@val-co.com 01133K





Our bins offer you

the most

efficient way

to manage

your feed.

Performance You Can Count On

Feed Bins

We Have The Right Size Bin To Meet Your Needs.


Automated Feed Systems Save Labor.

VAL-CO® Bulk Storage Bins are the ideal structure to protect feed from weather.

The weather tight die formed roof has reinforcing ribs at the seams for added strength and ease of assembly. The 22 inch diameter, warp resistant top lid closes tight to keep out moisture. Bin bolts have a built-in weather seal and a drip edge keeps water away from the taper hopper and unloading boot.

VAL-CO bins really perform with a 60 degree taper hopper on the 6 and 9 ft. bins and 67 degree on the 7 ft. bin. The tapers are offset to allow smooth feed flow and the top lid operates smoothly with either the chain or the pinch-lock opener.

VAL-CO bins are tough! Bin sheets are made of heavy gauge G-90 galvanized steel with 2-2/3" wide by 1/2" deep corrugation. Legs are die formed with a sturdy bracing system for structural support. High strength bolts are used throughout VAL-CO bins.



International: Phone: (+1) 419-678-8731



The VAL-CO Family

Watering Systems

• Feed Bins, Fill Systems

Feeders

Nests

Egg Collection Systems

Cage Equipment

• Brooders & Heaters

Evaporative Cooling

• Fans & Other Ventilation

• Whole House ControllersTM

Flooring

Incinerators

Alarms



VAL-CO® Flexible Auger Systems are the efficient way to deliver feed —

almost anywhere you need it! Installation is easy and maintenance costs are low. Components are all poly or heavy galvanized steel construction. Choose VAL-CO for versatility, top performance and long service life.

Components

A wide variety of components lets you build a feed delivery system to meet your exact requirements.




Flexible Auger

Flexible Auger for Low Volume, Standard Volume, High Volume, as well as high Moisture (up to 25°) and pellet applications.

Boots

Choose single 30°, single straight, or double straight poly upper boot transition. Lower boots (unloaders) are available for single, double or twin directional installations. All boots have a handy cleanout door.





Poly Drop Outlets

Three sizes are available with shutoffs and a variety of options to meet most any requirement.



Mechanical and electronic switches offer reliable system control — and the VAL-CO maximum run timer helps protect against feed wastage.





Discharge Heads

Discharge Heads with safety shutoff come prewired or water resistant. They are available in single or double line — and are a strong platform for gear or belt drive (not shown).

Flag System or Feed Line Extension

Flag System or Feed Line Extensions can be made with the accessories shown to the right.



